

Industralight IL2630 Comet Recessed LED Downlight

Industralight Comet is a LED downlight fixture suitable for commercial projects. The fittings feature semi-specular reflector for optimum efficiency and aesthetic. Comet LED downlights feature integrated LED with professionally designed thermal management system resulting in superior service life. Available in a range of dimming configurations and sizes from 20W to 50W.

ELECTRICAL PARAMETERS

Input Voltage	100-240VAC
Max Power Consumption	30W
LED Driver Classification	Remote Constant Current
Light Source Classification	Sharp COB LED

MECHANICAL SPECIFICATIONS

IP Protection Rating	IP44
Trim Diameter	190mm
Ceiling Cutout	170mm
Overall Depth	130mm
Recommended Operating Temp	15°C - 45°C

CONFIGURATION OPTIONS

Non standard trim colours available by special request

DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Light Source Efficacy	95lm/W
CCT Colour Temperatures	3000K / 4000K / 6500K
Colour Rendering Index [CRI]	→95
Beam Angle/Viewing Angle	60°

LIGHTING DESIGNS & SIMULATIONS

Industralight can provide independent LUX calculations and 3D lighting simulations for your project incorporating this product. Please contact our office for more information on design services.

DIMMING CONFIGURATION

Industralight Comet LED downlights are supplied with phase dimmable LED driver

DALI dimmable LED driver available by special request

Non-dimmable version available by special request

ORDERING INFORMATION

Series Model Number	IL2630
Specify Colour Temp	3000K / 4000K / 6500K
Specify Wattage	30W
Specify Dimming Configuration	Phase Dimmable / DALI / Non-Dim
Warranty Information	Extended Warranty Available

